

# IDIS DirectView™ Full HD Video Wall Monitors


with 3.6mm the World's narrowest bezel-to-bezel

55" 4 x 3 : Video Wall



Full-HD UNB Video Wall Monitor

DirectView™ **VW-F551**



Cutting-edge video wall monitor for surveillance control room

IDIS DirectView VW-F551 video wall monitor have been specially designed for use in control rooms with an array of surveillance-oriented features which well addresses the needs of security environments. VW-F551 advances video wall technology with the World's narrowest 3.6mm ultra-narrow bezel which provides seamless viewing experience with unrivalled image quality. Featuring 55-inch full-HD S-IPS LCD panel with LED backlight, the VW-F551 also provides exceptional reliability for 24/7 use in control room with a range of unique innovations that significantly reduces total cost of ownership with lower power consumption, maintenance cost and longer lifetime.

Full-HD UNB Video Wall Monitor

DirectView™ VW-F551




VW-F551

3.6mm Ultra-Narrow Bezel for seamless viewing experience



The VW-F551 features incredibly thin bezels at a mere 2.4mm (L/T) and 1.2mm (R/B) - 3.6mm bezel-to-bezel - shaving more than 33% off competition model. VW-F551 creates virtually seamless video walls for a more precise and impactful delivery of surveillance scenes, while minimizing viewing distractions,


DisplayPort 1.2 Daisy-Chain



Without any need of complex distributors, VW-F551 features digital daisy chain which supports up to 100 displays. Additionally, VW-F551 displays UHD resolution through DP 1.2 streaming without any additional equipment.



## Slim & Space-saving Design




VW-F551 is about 30% less in depth than conventional large format LCD displays which provides more space on your control room environment.

## LED Backlight Technology

IDIS Directview monitors features latest energy-saving LED backlight technology. Producing less heat than conventional CCFL backlights, Directview monitors reduce image burn-in while providing longer panel life.


## Clear Motion Display

Featuring the industry's most advanced S-IPS technology, DV-U1481 UHD surveillance monitor delivers clearer picture with faster response time of the moving objects.




## Anti-glare Coating

DirectView monitors feature anti-glare coating designed to reduce mirror-like reflections and improve screen viewing in challenging lighting conditions.



## VESA-compliant Mounting



VESA-compliant mounts enables safe and easy installation.

## Remote Control Unit

DirectView UHD Monitors come with a fully-functional remote controller which provides easier configuration and operation

## True Wide Viewing

DirectView monitors produce vivid and clear image from any viewing angle by maintaining high color fidelity, low gamma distortion and high contrast ratio.



## Eco-friendly, Low Power Consumption



With latest LED backlighting technology, VW-F551 provides exceptional energy efficiency with up to 30% than conventional CCFL monitors.

## Comprehensive Interfaces

To fulfil various surveillance standards, VW-F551 provides a wide variety of interfaces including HDMI, DP, VGA, DVI-D, Audio I/O, RS232 and USB.

## Longer Lifetime; 50,000 hours



Featuring advanced backlight control technique, VW-F551 provides industry-leading lifetime of 50,000 hours which accounts for 5 years of 24/7 operation.




Full-HD UNB Video Wall Monitor

# DirectView™ VW-F551

## SPECIFICATIONS

Model	VW-F551
Panel	
Screen Size	55 Inch
Max. Resolution	1920 x 1080 @ 60Hz
Panel Technology	IPS (In-Plane Switching)
Pixel Pitch	0.63mm (H) X 0.63mm (V)
Brightness	500 cd/m2
Contrast Ratio	1400 : 1
Aspect Ratio	16:9
Viewing Angle (H/V)	178° / 178°
Display Color	1.06 Billion (10bit)
Response Time	12ms
Refresh Rate	60Hz
Interface	
HDMI In	1
Display Port In / Out	1 / 1
VGA In	1
DVI In	1
BNC Video In	1
RS232 In / Out	1
External Control	Remote Control
IR Sensor	Remote Control
Serial IN/OUT	RS232-C Daisy Chain
USB	(for firmware update)
Transmitter	
Remote Control	Yes
Feature	
Power Savings (DPMS)	Yes
Anti-glare	Yes
General	
Outline Dimension (W x H x D)	47.7" x 26.94" x 3.39" 1213.4mm x 684.2mm x 86mm
Bezel	3.6mm (Bezel to Bezel)
Net Weight	24kg
Material / Color	Metal / Black
Warranty - Parts / Labor	3 year / 3 year
MTBF	60,000 Hours
Power Supply	AC 110~127V 50/60Hz, 220~240 50/60Hz
Power Consumption	240W
Operating Temperature	5°C ~ 35°C
Storage Temperature	-0°C ~ 40°C
Mount	
VESA Mount Size	600x400mm

## DIMENSION



### IDIS HQ

IDIS Tower, 344 Pangyo-ro  
Bundang-gu, Seongnam-si  
Gyeonggi-do  
Republic of Korea, 463-400

T +82 (0)31 723 5400  
F +82 (0)31 723 5100  
E sales@idisglobal.com

### IDIS America

801 Hammond St, Suite 200  
Coppell, TX 75019  
U.S.A

T +1 469 464 3590  
F +1 469 464 4449  
E americas@idisglobal.com

### IDIS Europe

1000 Great West Road  
Brentford, Middlesex  
TW8 9HH  
The United Kingdom

T +44 (0)203 657 5678  
F +44 (0)203 697 9360  
E uksales@idisglobal.com

### IDIS Benelux

De Slof 9  
5107 RH  
Dongen  
The Netherlands

T +31 (0)162 387247  
F +31 (0)162 311915  
E sales@bnl.idisglobal.com

### IDIS Middle East

P.O. Box 341037  
D-308, DSO HQ Bldg,  
Dubai Silicon Oasis,  
Dubai, U.A.E

T +971 4 501 5434  
F +971 4 501 5436  
E sales\_mena@idisglobal.com

IDIS and identifying product names and numbers herein are registered trademarks of IDIS Co., Ltd. All non-IDIS brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.  
Copyright © IDIS Co., Ltd. All rights reserved.

For more information, please visit  
[www.idisglobal.com](http://www.idisglobal.com)